

Technical Information Sheet

Durite Flexible Starter Cables

Specification

Single insulated flexible battery cable designed for use in tough working environments. Resistant to petrol, lubricating oils and diluted acids.

Specification: BS6862
Temp Range: -30Deg to +70Deg C
Insulation: Polyvinyl Chloride (PVC)
Stranding: Plain copper wires

Cable Specs and Dimensions

Cross Section (mm ²)	Part Number	Copper Wires	Nominal Current Rating (Amps)	Resistance @20DegC (Ohms)	Overall dia (mm)
16	0-978-XX-F	224/0.30mm	110A	0.00126	9
20	0-980-XX-F	266/0.30mm	135A	0.00096	9.5
25	0-981-XX-F	196/0.40mm	170A	0.00077	9.7
35	0-976-XX-F	451/0.30mm	240A	0.00056	11.7
40	0-982-XX-F	315/0.40mm	300A	0.00050	12.2
50	0-977-1X-F	640/0.30mm	345A	0.00039	13.5
60	0-983-XX-F	475/0.40mm	415A	0.00033	14.6
70	0-977-0X-F	905/0.30mm	485A	0.00029	15.8

The information provided in this document is correct to the best of our knowledge at time of printing. However, specifications may change at any time without notice.